

13oz/ 440gsm Frontlit Banner

PRODUCT: B02-440

FEATURES / APPLICATIONS:

- White opaque substrate for frontlit display & billboard
- Indoor or outdoor frontlit display under moderate weather conditions
- Smooth surface
- Vibrantly and consistent printing quality
- Matte & gloss surfaces available

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	440g/m ²	13oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060	550 x 550 dtex	500 x 500 denier
Tensile Strength	DIN EN ISO 1421	845x648 N/5cm	98x75 lbs/inch
Tear Strength	DIN 53363	150x110N	34x 27lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	DIN 4102	NFPA 701, B1, M2	
Width	N/A	Max 320cm	126 Inch

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	
<input type="checkbox"/>			

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690
F. 0086-571-28918695

Soyang Europe Ltd

38 Peel Industrial Estate, Bury, Manchester BL9 0LU UK.

www.soyang.co.uk

P. 0044-870 112 7445
F. 0044-870 112 7446

Soyang Europe B.V. (Europe Warehouse)

Van der Helm - Hudig Moerdijk B.V. Orionweg 6-8, 4782 SC Moerdijk The Netherlands

www.soyang.co.uk

P. 0044-870 112 7445
F. 0044-870 112 7446